

SNYDER



Equipment, Inc.

Storing, Rolling, Lifting since 1947

PRODUCT INFORMATION

PRESTO STACKERS

2946 Larimer St. Denver, CO 80205
303-295-1100 / 800-373-7693
FAX 303-295-2464
Email info@snyderequipment.com
www.snyderequipment.com

Straddle Stackers

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
B800 Series - 20" Load Center							
B862-1500	1500 lbs	62"	2"	80"x32"x54"	26" / 32"	5" / 4"	575 lbs
B874-1500	1500 lbs	74"	2"	92"x32"x54"	26" / 32"	5" / 4"	600 lbs
B886-1500	1500 lbs	86"	2"	104"x32"x54"	26" / 32"	5" / 4"	620 lbs
B862-2000	2000 lbs	62"	2 1/2"	80"x32"x54"	26" / 32"	5" / 4"	585 lbs
B874-2000	2000 lbs	74"	2 1/2"	92"x32"x54"	26" / 32"	5" / 4"	610 lbs
B886-2000	2000 lbs	86"	2 1/2"	104"x32"x54"	26" / 32"	5" / 4"	630 lbs
BT800 Series - 20" Load Center							
BT894-1500	1500 lbs	94"	2 1/2"	119"773"x38"x55"	32" / 38"	5" / 4"	810 lbs
BT8107-1500	1500 lbs	107"	2 1/2"	133"811"x38"x55"	32" / 38"	5" / 4"	870 lbs
BT8127-1500	1500 lbs	127"	2 1/2"	153"993"x38"x55"	32" / 38"	5" / 4"	920 lbs
BT894-2000	2000 lbs	94"	2 1/2"	119"773"x38"x55"	32" / 38"	5" / 4"	830 lbs
BT8107-2000	2000 lbs	107"	2 1/2"	133"811"x38"x55"	32" / 38"	5" / 4"	880 lbs
BT8127-2000	2000 lbs	127"	2 1/2"	153"993"x38"x55"	32" / 38"	5" / 4"	930 lbs

Features

- 1500 - 2000 lb. capacity
- 20" load centers
- Lifting heights - 62" through 127"
- Fixed and telescopic mast
- 30" solid steel adjustable forks
- Hand operated floor lock
- Flow control valve for smooth lowering
- Lifting speed 5" per second
- Fixed base
- Heavy-duty 12 volt deep cycle battery
- Built-in tapering battery charger
- Optional fifth wheel for greater mobility
- Leaf type chains with 8250 lb. yield point
- High impact phenolic load wheels



Pallet Stackers

- 1500 - 2700 lb capacity
- 24" load centers
- Lifting heights - 62" through 144"
- Fixed and telescopic mast
- 36" solid steel adjustable forks
- Hand-operated floor lock
- Lifting speed 4" per second
- Fixed or adjustable base
- Heavy-duty 12 volt deep cycle battery
- Built-in tapering battery charger
- Fifth wheel for greater mobility
- Leaf-type chains with 8250 lb yield point



Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
PS Series - 42" I.D. Straddle - 24" Load Center							
PS262	2000 lbs	62"	2 1/2"	80"x48"x70"	42"/48"	5" / 4"	825 lbs
PS274	2000 lbs	74"	2 1/2"	92"x48"x70"	42"/48"	5" / 4"	875 lbs
PS286	2000 lbs	86"	2 1/2"	104"x48"x70"	42"/48"	5" / 4"	925 lbs
PS2762	2700 lbs	60"	2 1/2"	80"x48"x70"	42"/48"	5" / 4"	950 lbs
PS2774	2700 lbs	72"	2 1/2"	92"x48"x70"	42"/48"	5" / 4"	995 lbs
PS50 Series - 50" I.D. Straddle - 24" Load Center							
PS62-50	1500 lbs	62"	2 1/2"	80"x56"x70"	50"/56"	5" / 4"	825 lbs
PS74-50	1500 lbs	74"	2 1/2"	92"x56"x70"	50"/56"	5" / 4"	875 lbs
PS86-50	1500 lbs	86"	2 1/2"	104"x56"x70"	50"/56"	5" / 4"	925 lbs
PS262-50	2000 lbs	62"	2 1/2"	80"x56"x70"	50"/56"	5" / 4"	850 lbs
PS274-50	2000 lbs	74"	2 1/2"	92"x56"x70"	50"/56"	5" / 4"	925 lbs
PS286-50	2000 lbs	86"	2 1/2"	104"x56"x70"	50"/56"	5" / 4"	950 lbs
PS2762-50	2700 lbs	60"	2 1/2"	80"x56"x70"	50"/56"	5" / 4"	975 lbs
PS2774-50	2700 lbs	72"	2 1/2"	92"x56"x70"	50"/56"	5" / 4"	1020 lbs
PSA Series - Adjustable Base - Straddle - (35" I.D. to 50" I.D.) - 24" Load Center							
PSA62	1500 lbs	62"	2 1/2"	80"x41"-56"x72"	35"-50"/41"-56"	5" / 5"	945 lbs
PSA74	1500 lbs	74"	2 1/2"	92"x41"-56"x72"	35"-50"/41"-56"	5" / 5"	995 lbs
PSA86	1500 lbs	86"	2 1/2"	104"x41"-56"x72"	35"-50"/41"-56"	5" / 5"	1045 lbs
PSA262	2000 lbs	62"	2 1/2"	80"x41"-56"x72"	35"-50"/41"-56"	5" / 5"	950 lbs
PSA274	2000 lbs	74"	2 1/2"	92"x41"-56"x72"	35"-50"/41"-56"	5" / 5"	995 lbs
PSA286	2000 lbs	86"	2 1/2"	104"x41"-56"x72"	35"-50"/41"-56"	5" / 5"	1050 lbs
PSA2762	2700 lbs	60"	2 1/2"	80"x41"-56"x72"	35"-50"/41"-56"	5" / 5"	1095 lbs
PSA2774	2700 lbs	72"	2 1/2"	92"x41"-56"x72"	35"-50"/41"-56"	5" / 5"	1125 lbs
PST Series - 42" I.D. Straddle - Telescopic Mast - 24" Load Center							
PST294	2000 lbs	94"	2 1/2"	119"/73"x48"x71"	42"-48"	5" / 4"	950 lbs
PST2107	2000 lbs	107"	2 1/2"	133"/81"x48"x71"	42"-48"	5" / 4"	1000 lbs
PST2127	2000 lbs	127"	2 1/2"	153"/93"x48"x71"	42"-48"	5" / 4"	1050 lbs
PST2144	2000 lbs	144"	2 1/2"	170"/99"x48"x71"	42"-48"	5" / 4"	1100 lbs
PST2794	2700 lbs	94"	2 1/2"	119"/73"x48"x71"	42"-48"	5" / 4"	1140 lbs
PST27107	2700 lbs	107"	2 1/2"	133"/81"x48"x71"	42"-48"	5" / 4"	1190 lbs
PST27127	2700 lbs	127"	2 1/2"	153"/93"x48"x71"	42"-48"	5" / 4"	1240 lbs
PST50 Series - 50" I.D. Straddle - Telescopic Mast - 24" Load Center							
PST294-50	2000 lbs	94"	2 1/2"	119"/73"x56"x71"	50"-56"	5" / 4"	960 lbs
PST2107-50	2000 lbs	107"	2 1/2"	133"/81"x56"x71"	50"-56"	5" / 4"	1010 lbs
PST2127-50	2000 lbs	127"	2 1/2"	153"/93"x56"x71"	50"-56"	5" / 4"	1060 lbs
PST2144-50	2000 lbs	144"	2 1/2"	170"/99"x56"x71"	50"-56"	5" / 4"	1120 lbs
PST2794-50	2700 lbs	94"	2 1/2"	119"/73"x56"x71"	50"-56"	5" / 4"	1150 lbs
PST27107-50	2700 lbs	107"	2 1/2"	133"/81"x56"x71"	50"-56"	5" / 4"	1200 lbs
PST27127-50	2700 lbs	127"	2 1/2"	153"/93"x56"x71"	50"-56"	5" / 4"	1250 lbs
PSTA SERIES - Adjustable Base - Straddle - (35" I.D. to 50" I.D.) - 24" Load Center							
PSTA294	2000 lbs	94"	2 1/2"	119"/73"x41"-56"x73"	35"-50"/41"-56"	5" / 5"	1100 lbs
PSTA2107	2000 lbs	107"	2 1/2"	133"/81"x41"-56"x73"	35"-50"/41"-56"	5" / 5"	1150 lbs
PSTA2127	2000 lbs	127"	2 1/2"	153"/93"x41"-56"x73"	35"-50"/41"-56"	5" / 5"	1200 lbs
PSTA2794	2700 lbs	94"	2 1/2"	119"/73"x41"-56"x73"	35"-50"/41"-56"	5" / 5"	1350 lbs
PSTA27107	2700 lbs	107"	2 1/2"	133"/81"x41"-56"x73"	35"-50"/41"-56"	5" / 5"	1400 lbs
PSTA27127	2700 lbs	127"	2 1/2"	153"/93"x41"-56"x73"	35"-50"/41"-56"	5" / 5"	1450 lbs