

SNYDER

Equipment, Inc.

Storing, Rolling, Lifting since 1947



PRODUCT INFORMATION

PRESTO WORK POSITIONERS

2946 Larimer St. Denver, CO 80205
303-295-1100 / 800-373-7693
FAX 303-295-2464
Email info@snyderequipment.com
www.snyderequipment.com



Non-Straddle Work Positioners

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
WP Series - Non-Straddle - 24" Load Center							
WP36-20	2000 lbs	36"	3 1/4"	60"x28"x65"	14" / 26 1/2"	3" / 8"	660 lbs
WP48-20	2000 lbs	48"	3 1/4"	72"x28"x65"	14" / 26 1/2"	3" / 8"	720 lbs
WP60-20	2000 lbs	60"	3 1/4"	84"x28"x65"	14" / 26 1/2"	3" / 8"	770 lbs
WP36-30	3000 lbs	36"	3 1/4"	60"x28"x65"	14" / 26 1/2"	3" / 8"	710 lbs
WP48-30	3000 lbs	48"	3 1/4"	72"x28"x65"	14" / 26 1/2"	3" / 8"	750 lbs
WP60-30	3000 lbs	60"	3 1/4"	84"x28"x65"	14" / 26 1/2"	3" / 8"	800 lbs

Features

- 2000 - 3000 lb. capacity
- 24" load centers
- Lifting heights - 36" through 60"
- Fixed mast
- 42" steel forks
- 42" lowered height
- Steering wheel for greater mobility
- Lifting speed 4" per second
- Fixed base
- Heavy-duty deep cycle battery
- Built-in tapering battery charger
- Hand operated floor lock
- Phenolic front load wheels
- Polyurethane rear wheels
- Optional slip-on platforms available
- 48" long forks available

Straddle Work Positioners

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
WPS42 Series - 42" I.D. - 24" Load Center							
WPS4236-20	2000 lbs	36"	2"	59"x48"x65"	42" / 48"	5" / 8"	670 lbs
WPS4248-20	2000 lbs	48"	2"	71"x48"x65"	42" / 48"	5" / 8"	695 lbs
WPS4260-20	2000 lbs	60"	2"	83"x48"x65"	42" / 48"	5" / 8"	720 lbs
WPS4236-30	3000 lbs	36"	2"	59"x48"x65"	42" / 48"	5" / 8"	700 lbs
WPS4248-30	3000 lbs	48"	2"	71"x48"x65"	42" / 48"	5" / 8"	725 lbs
WPS4260-30	3000 lbs	60"	2"	83"x48"x65"	42" / 48"	5" / 8"	750 lbs
WPS50 Series - 50" I.D. - 24" Load Center							
WPS5036-20	2000 lbs	36"	2"	59"x56"x65"	50" / 56"	5" / 8"	680 lbs
WPS5048-20	2000 lbs	48"	2"	71"x56"x65"	50" / 56"	5" / 8"	705 lbs
WPS5060-20	2000 lbs	60"	2"	83"x56"x65"	50" / 56"	5" / 8"	730 lbs
WPS5036-30	3000 lbs	36"	2"	59"x56"x65"	50" / 56"	5" / 8"	710 lbs
WPS5048-30	3000 lbs	48"	2"	71"x56"x65"	50" / 56"	5" / 8"	735 lbs
WPS5060-30	3000 lbs	60"	2"	83"x56"x65"	50" / 56"	5" / 8"	760 lbs

Features

- 2000 - 3000 lb. capacity
- 24" load centers
- Lifting heights - 36" through 60"
- Fixed mast
- 42" steel forks
- 2" lowered height
- Steering wheel for greater mobility
- Lifting speed 4" per second
- Fixed base
- Heavy-duty 12 volt deep cycle battery
- Built-in tapering battery charger
- Hand operated floor lock
- Phenolic front load wheels
- Polyurethane rear wheels
- Optional slip-on platforms available
- 48" long forks available

