



PRODUCT INFORMATION

PRESTO PNEUMATIC LIFT TABLES

2946 Larimer St. Denver, CO 80205
303-295-1100 / 800-373-7693
FAX 303-295-2464
Email info@snyderequipment.com
www.snyderequipment.com

Pneumatic Scissor Lifts & Rotate



Shown with optional accordion skirting

Model Number	Lift Capacity	Vertical Travel	Lowered Height	Raised Height	Base Size W / L	Platform Size W / L	Shipping Weight
AXR10 Series							
AXR10 - 3648	1000 lbs	21"	11"	32"	36" x 48"	36" x 48"	1005 lbs
AXR10 - 4848	1000 lbs	21"	11"	32"	36" x 48"	48" x 48"	1135 lbs
AXR10 - 4856	1000 lbs	21"	11"	32"	36" x 48"	56" x 48"	1230 lbs
AXR10 - 4860	1000 lbs	21"	11"	32"	36" x 48"	60" x 48"	1270 lbs
AXR20 Series							
AXR20 - 3648	2000 lbs	24"	11"	35"	36" x 48"	36" x 48"	1105 lbs
AXR20 - 4848	2000 lbs	24"	11"	35"	36" x 48"	48" x 48"	1245 lbs
AXR20 - 4856	2000 lbs	24"	11"	35"	36" x 48"	56" x 48"	1335 lbs
AXR20 - 4860	2000 lbs	24"	11"	35"	36" x 48"	60" x 48"	1400 lbs
AXR40 Series							
AXT40 - 4848	4000 lbs	24"	11"	35"	48" x 48"	48" x 48"	1370 lbs
AXT40 - 4856	4000 lbs	24"	11"	35"	48" x 48"	56" x 48"	1500 lbs
AXT40 - 4860	4000 lbs	24"	11"	35"	48" x 48"	60" x 48"	1545 lbs

Features

- 1000 - 4000 lb. capacity
- 21" & 24" vertical travel
- Turntable
- Pedestal mounted control
- Optional foot control
- Lifetime warranty on Firestone Actuator
- Air requirements 80 psi @ 15 cfm
- AXR units designed for stationary use
- Optional Turret bearing system
- Custom designs available

Heavy Duty Pneumatic Scissor Lift & Rotate

Model Number	Lift Capacity	Vertical Travel	Lowered Height	Raised Height	Base Size W / L	Platform Size W / L	Shipping Weight
AXSR20 Series							
AXSR20-3648	2000 lbs	24"	15"	39"	36" x 48"	36" x 48"	1105 lbs
AXSR20-4848	2000 lbs	24"	15"	39"	36" x 48"	48" x 48"	1245 lbs
AXSR20-4856	2000 lbs	24"	15"	39"	36" x 48"	56" x 48"	1335 lbs
AXSR20-4860	2000 lbs	24"	15"	39"	36" x 48"	60" x 48"	1400 lbs
AXSR40 Series							
AXSR40-3648	4000 lbs	24"	15"	39"	36" x 48"	36" x 48"	1320 lbs
AXSR40-4848	4000 lbs	24"	15"	39"	36" x 48"	48" x 48"	1370 lbs
AXSR40-4856	4000 lbs	24"	15"	39"	36" x 48"	56" x 48"	1500 lbs
AXSR40-4860	4000 lbs	24"	15"	39"	36" x 48"	60" x 48"	1545 lbs
AXSR60 Series							
AXSR60-4848	6000 lbs	24"	15"	39"	48" x 48"	48" x 48"	1570 lbs
AXSR60-4856	6000 lbs	24"	15"	39"	48" x 48"	56" x 48"	1700 lbs
AXSR60-4860	6000 lbs	24"	15"	39"	48" x 48"	60" x 48"	1745 lbs
AXSR80 Series							
AXSR80-4848	8000 lbs	24"	15"	39"	48" x 48"	48" x 48"	1670 lbs
AXSR80-4856	8000 lbs	24"	15"	39"	48" x 48"	56" x 48"	1800 lbs
AXSR80-4860	8000 lbs	24"	15"	39"	48" x 48"	60" x 48"	1845 lbs



Features

- 2000 - 8000 lb. capacity
- 24" travel
- Turntable
- Air requirements 80 psi @ 15 cfm
- Lifetime warranty on Firestone Actuator
- Optional Turret bearing system
- Pedestal mounted control
- Optional foot or hand control
- AXSR units available in transportable version
- No floor lagging necessary
- Oversized platforms available
- Custom design available

Pneumatic Scissor Lifts

Model Number	Lift Capacity	Vertical Travel	Lowered Height	Raised Height	Base Size W / L	Platform Size W / L	Shipping Weight
AX10 Series							
AX10 - 3648	1000 lbs	21"	8"	29"	36" x 48"	36" x 48"	770 lbs
AX10 - 4848	1000 lbs	21"	8"	29"	36" x 48"	48" x 48"	840 lbs
AX10 - 4856	1000 lbs	21"	8"	29"	36" x 48"	56" x 48"	885 lbs
AX10 - 4860	1000 lbs	21"	8"	29"	36" x 48"	60" x 48"	910 lbs
AX20 Series							
AX20 - 3648	2000 lbs	24"	8"	32"	36" x 48"	36" x 48"	805 lbs
AX20 - 4848	2000 lbs	24"	8"	32"	36" x 48"	48" x 48"	865 lbs
AX20 - 4856	2000 lbs	24"	8"	32"	36" x 48"	56" x 48"	905 lbs
AX20 - 4860	2000 lbs	24"	8"	32"	36" x 48"	60" x 48"	990 lbs
AX40 Series							
AX40 - 4848	4000 lbs	24"	8"	32"	48" x 48"	48" x 48"	990 lbs
AX40 - 4856	4000 lbs	24"	8"	32"	48" x 48"	56" x 48"	1065 lbs
AX40 - 4860	4000 lbs	24"	8"	32"	48" x 48"	60" x 48"	1085 lbs

Features

- 1000 - 4000 lb. capacity
- 21" & 24" travel
- 8" lowered height
- 32" raised height
- Air requirements - 80 psi @ 15 cfm
- Lifetime warranty on Firestone Actuator
- Pedestal mounted control
- Optional foot or hand control
- AX units designed for stationary use
- Custom platform available



Heavy Duty Pneumatic Scissor Lifts



Model Number	Lift Capacity	Vertical Travel	Lowered Height	Raised Height	Base Size W / L	Platform Size W / L	Shipping Weight
AXS20 Series							
AXS20 - 3648	2000 lbs	24"	12"	36"	36" x 48"	36" x 48"	805 lbs
AXS20 - 4848	2000 lbs	24"	12"	36"	36" x 48"	48" x 48"	865 lbs
AXS20 - 4856	2000 lbs	24"	12"	36"	36" x 48"	56" x 48"	905 lbs
AXS20 - 4860	2000 lbs	24"	12"	36"	36" x 48"	60" x 48"	990 lbs
AXS40 Series							
AXS40 - 3648	4000 lbs	24"	12"	36"	36" x 48"	36" x 48"	970 lbs
AXS40 - 4848	4000 lbs	24"	12"	36"	36" x 48"	48" x 48"	990 lbs
AXS40 - 4856	4000 lbs	24"	12"	36"	36" x 48"	56" x 48"	1065 lbs
AXS40 - 4860	4000 lbs	24"	12"	36"	36" x 48"	60" x 48"	1085 lbs
AXS60 Series							
AXS60 - 4848	6000 lbs	24"	12"	36"	48" x 48"	48" x 48"	1120 lbs
AXS60 - 4856	6000 lbs	24"	12"	36"	48" x 48"	56" x 48"	1265 lbs
AXS60 - 4860	6000 lbs	24"	12"	36"	48" x 48"	60" x 48"	1285 lbs
AXS80 Series							
AXS80 - 4848	8000 lbs	24"	12"	36"	48" x 48"	48" x 48"	1290 lbs
AXS80 - 4856	8000 lbs	24"	12"	36"	48" x 48"	56" x 48"	1365 lbs
AXS80 - 4860	8000 lbs	24"	12"	36"	48" x 48"	60" x 48"	1385 lbs

Features

- 2000 - 8000 lb. capacity
- 24" travel
- 36" raised heights
- Air requirements 80 psi @ 15 cfm
- Lifetime warranty on Firestone Actuator
- Pedestal mounted control
- Optional foot or hand control
- AXS units available in transportable version
- No floor lagging necessary
- Custom platforms available

Pallet Positioner

Model Number	Lift Capacity	Base Size W / L	Vertical Travel	Lowered Height	Raised Height	Platform Size	Shipping Weight	List Price
AccuLoad Series								
AL - 30	3000 lbs	24" x 48"	21"	9 1/4"	30 1/4"	43" dia.	450 lbs	————

Features

- 3000 lb. capacity
- 21" vertical travel
- Foot Control standard
- Optional pedestal control available
- 3/8" x 43" solid rotating platform
- Lifetime warranty on Firestone Actuator
- Optional portability package available
- Air requirements 80 psi @ 15 cfm
- Custom platforms available
- Custom designs available



Mechanical Options

Description and Specification	List Price
Oversized Platform - platforms can be increased in width and length up to additional 24". Side and end load capacities are derated 2% per inch of increase and oversized models must be lagged to the floor.	_____
Platform with Beveled Edges - welded at 30 degree angles, increases the standard platform by 4" on all sides	_____
Pit Mounted Units - for ground level applications require a Platform with Beveled Edges. Lifting Eyes required for installation.	See Option
Lifting Eyes - provided for installation and transporting of unit with a sling or lifting chain	_____
Portable Units - wheeled dolly handle and two 5" fixed wheels (specify side or end mounting) for moving empty lifts. Overall lowered height is not changed when unit is in an operating position.	_____
Oversized Platform	_____
Transportable Units - 6" steel casters, two fixed and two swivel, and a Presto floor lock mounted underneath base frame. Adds 9 3/4" to the lowered height only available on AXS, AXSR, and AXST.	_____
Oversized Platform	_____
V Grooved Wheels - 5" steel wheels for Transportable Units only, sold per pair.	_____
Ball Transfer Tops - for multi directional movement of work loads, available for all load weights. Adds 2" to overall lowered height.	_____
Floor Stands - designed to increase the lowered height of tilters	_____
Motion Stabilizer - reduces the "bounce" found in pneumatic tilt tables.	_____

Description and Specification	List Price
Detent Stops - manual or spring activated stops for a Turntable, standard stops positioned at 90 degree increments	Manual _____ Spring _____
Positioning Lock - Pneumatically actuated lock for turntable tops, securely locks the turntable in any position. Must be used in conjunction with a Turret bearing system.	_____
Conveyor Top - mounted to the lift table platform these 1.9" diameter rollers on 3" center have a 1000 lb capacity per linear foot. Adds 4" to overall height	_____
24" x 36" platform	_____
24" x 48" platform	_____
24" x 64" platform	_____
Custom sizes and designs available	_____
Conveyor Sides - used to retain product on conveyor tops, recommend on all Transporting Units.	_____
Fixed 3" sides	_____
Movable 3" sides	_____
Optional Top Material - for special handling of loads, v tops, aluminum material, stainless steel, diamond plate, etc.	_____
Accordion (Bellow) Skirts - designed to cover to scissor leg assemble of the lift table.	_____
Fork Pockets - used for moving scissor lifts between work stations.	_____
Increased Vertical Travel - can be achieved by stacking two air bags, call with your application.	_____
Degree of Tilt - can be increased on pneumatic tilts by stacking two air bags, call with you application.	_____