

SNYDER



Equipment, Inc.

Storing, Rolling, Lifting since 1947

PRODUCT INFORMATION

PRESTO SMALL STACKERS

2946 Larimer St. Denver, CO 80205
303-295-1100 / 800-373-7693
FAX 303-295-2464
Email info@snyderequipment.com
www.snyderequipment.com

Battery Operated Stacker

- 1000 - 2000 lb capacity
- 15" load center
- Lifting heights - 52" - 78"
- Fixed mast
- 25" solid steel adjustable forks
- Floor saving phenolic wheels
- Perforated metal safety screen
- Lifting speed 5" per second
- Fixed base
- Heavy-duty deep cycle battery
- Built-in tapering battery charger
- Foot operated floor lock
- Leaf type chain with 8250 lb yield point
- Optional 24" x 24" slip on platform



Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
B600 Series - Adjustable 25" Forks (Non-Straddle) - 15" Load Center							
B652	1000 lbs	52"	5 1/4"	66"x27"x49"	15" / 21"	5" / 5"	450 lbs
B666	1000 lbs	66"	5 1/4"	80"x27"x49"	15" / 21"	5" / 5"	470 lbs
B678	1000 lbs	78"	5 1/4"	92"x27"x49"	15" / 21"	5" / 5"	490 lbs
B652-1500	1500 lbs	52"	5 1/4"	66"x27"x49"	15" / 22"	5" / 5"	480 lbs
B666-1500	1500 lbs	66"	5 1/4"	80"x27"x49"	15" / 22"	5" / 5"	500 lbs
B678-1500	1500 lbs	78"	5 1/4"	92"x27"x49"	15" / 22"	5" / 5"	520 lbs
B652-2000	2000 lbs	52"	5 1/4"	66"x27"x49"	20" / 26"	5" / 5"	500 lbs
B666-2000	2000 lbs	66"	5 1/4"	80"x27"x49"	20" / 26"	5" / 5"	520 lbs
B678-2000	2000 lbs	78"	5 1/4"	92"x27"x49"	20" / 26"	5" / 5"	540 lbs

Drum Stackers

- 1000 lb capacity
- 18" load centers
- Lifting heights - 48" through 86"
- 30" solid steel forks
- Manual & battery operated
- Optional drum grabber attachment
- Forks bolted at 15" I.D. for 55 gallon drum
- Forks bolted at 11 1/2" I.D. for 30-gallon drum



Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
DSM Series - Manually Operated - 30" Forks - 18" Load Center							
D48	1000 lbs	48"	1 1/2"	66"x32"x48"	26" / 32"	5" / 4"	330 lbs
D62	1000 lbs	62"	1 1/2"	80"x32"x48"	26" / 32"	5" / 4"	350 lbs
D74	1000 lbs	74"	1 1/2"	92"x32"x48"	26" / 32"	5" / 4"	370 lbs
DSM Series - Battery Operated - 30" Forks - 18" Load Center							
D662	1000 lbs	62"	1 1/2"	80"x32"x52"	26" / 32"	5" / 4"	500 lbs
D674	1000 lbs	74"	1 1/2"	92"x32"x52"	26" / 32"	5" / 4"	530 lbs
D686	1000 lbs	86"	1 1/2"	104"x32"x52"	26" / 32"	5" / 4"	540 lbs

A/C Electric Stackers

- 1000 lb capacity
- 18" load centers
- Lifting heights - 52" through 130"
- Fixed and telescopic masks
- Stationary & portable units
- Lifting speed 4" per seconds
- Standard 3/4 HP 115/1/60 motor
- Optional motors available
- Optional slip on 32" x 30" platform
- Custom platforms
- Optional remote control
- Leaf-type chains with 8250 lb yield point
- 1500 & 2000 lb capacities available



Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
EP Series - Portable - 30" Forks - 18" Load Center							
EL752	1000 lbs	52"	5 1/4"	66"x32"x47"	24" / 30"	5" / 4"	395 lbs
EL766	1000 lbs	68"	5 1/4"	80"x32"x47"	24" / 30"	5" / 4"	415 lbs
EL778	1000 lbs	78"	5 1/4"	92"x32"x47"	24" / 30"	5" / 4"	435 lbs
ES Series - Stationary - 30" Forks - 18" Load Center							
EL750	1000 lbs	50"	3 1/4"	64"x32"x45"	24" / 30"	N/A	375 lbs
EL764	1000 lbs	64"	3 1/4"	78"x32"x45"	24" / 30"	N/A	395 lbs
EL776	1000 lbs	76"	3 1/4"	90"x32"x45"	24" / 30"	N/A	415 lbs
EL782	1000 lbs	82"	3 1/4"	96"x32"x45"	24" / 30"	N/A	425 lbs
EL788	1000 lbs	88"	3 1/4"	102"x32"x45"	24" / 30"	N/A	435 lbs
EL794	1000 lbs	94"	3 1/4"	108"x32"x45"	24" / 30"	N/A	515 lbs
EL7106	1000 lbs	106"	3 1/4"	120"x40"x45"	34" / 40"	N/A	555 lbs
EL7118	1000 lbs	118"	3 1/4"	132"x40"x45"	34" / 40"	N/A	585 lbs
ET Series - Portable - 30" Forks - 18" Load Center							
ET796	1000 lbs	94"	5 1/4"	111"66"x40"66"	34" / 40"	5" / 5"	570 lbs
ET7110	1000 lbs	110"	5 1/4"	133"81"x40"68"	34" / 40"	5" / 5"	620 lbs
ET7130	1000 lbs	130"	5 1/4"	153"93"x40"68"	34" / 40"	5" / 5"	685 lbs

Counterweight Stackers

- 1000 lb capacity
- 13" & 15" load centers
- Lifting heights - 62" & 74"
- Lifting speed 5" per second
- No outriggers
- Built-in tapering battery charger
- Heavy-duty deep cycle battery



- 25" or 30" solid steel adjustable forks

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Wheel Dia. Front/Rear	Shipping Weight	List Price
CW Series - Adjustable 25" Forks - 13" Load Center							
C62	1000 lbs	62"	1"	80"x27"x36"	5" / 5"	570 lbs	-----
C74	1000 lbs	74"	1"	92"x27"x36"	5" / 5"	590 lbs	-----
CW Series - Adjustable 30" Forks - 15" Load Center							
C62-15	1000 lbs	62"	1"	80"x27"x41"	5" / 5"	570 lbs	-----
C74-15	1000 lbs	74"	1"	92"x27"x41"	5" / 5"	590 lbs	-----
Overall length on C62 & C74 is 61" and on C62-15 & C74-15 is 71" C62-15 & C74-15 must be ordered with a minimum of 600 lbs of counter weight							

Lifting Weight	Counter Weight
1-200 lbs	150 lbs
200-399 lbs	300 lbs
400-599 lbs	400 lbs
600-799 lbs	500 lbs
800-1000 lbs	600 lbs

Hand Operated Stackers

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
M800 Series - Adjustable 30" Forks (Straddle) - 18" Load Center							
M852-2000	2000 lbs	50"	3 1/4"	66"x32"x51"	26" / 32"	5" / 5"	410 lbs
M866-2000	2000 lbs	64"	3 1/4"	80"x32"x51"	26" / 32"	5" / 5"	430 lbs
M878-2000	2000 lbs	76"	3 1/4"	92"x32"x51"	26" / 32"	5" / 5"	450 lbs

Features

- 2000 lb. capacity @ 18" load center
- Lifting heights - 50" through 76"
- Slip on 32" x 30" platform available
- Solid steel adjustable forks
- Hand operated pump
- Lift time approximately 1/2" per second
- Perforated metal safety screen
- Foot-operated safety floor lock
- Leaf type chain with 8250 lbs. yield point
- High impact floor saving phenolic wheels



Foot Operated Stackers

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
M100 Series - Platform (24" W x 24" L) - 15" Load Center							
M162	1000 lbs	52"	5 1/4"	66"x26"x38"	15" / 21"	5" / 4"	220 lbs
M166	1000 lbs	66"	5 1/4"	80"x26"x38"	15" / 21"	5" / 4"	240 lbs
M178	1000 lbs	78"	5 1/4"	92"x26"x38"	15" / 21"	5" / 4"	250 lbs
M300 Series - Platform (32" W x 30" L) - 18" Load Center							
M352	1000 lbs	52"	5 1/4"	66"x32"x44"	24" / 30"	5" / 4"	300 lbs
M366	1000 lbs	66"	5 1/4"	80"x32"x44"	24" / 30"	5" / 4"	320 lbs
M378	1000 lbs	78"	5 1/4"	92"x32"x44"	24" / 30"	5" / 4"	340 lbs
M200 Series - Adjustable 25" Forks (Non-Straddle) - 15" Load Center							
M252	1000 lbs	52"	5 1/4"	66"x27"x42"	15" / 21"	5" / 4"	290 lbs
M266	1000 lbs	66"	5 1/4"	80"x27"x42"	15" / 21"	5" / 4"	310 lbs
M278	1000 lbs	78"	5 1/4"	92"x27"x42"	15" / 21"	5" / 4"	330 lbs
M400 Series - Adjustable 30" Forks (Straddle) - 18" Load Center							
M452	1000 lbs	50"	3 1/4"	66"x32"x49"	26" / 32"	5" / 4"	320 lbs
M466	1000 lbs	64"	3 1/4"	80"x32"x49"	26" / 32"	5" / 4"	340 lbs
M478	1000 lbs	76"	3 1/4"	92"x32"x49"	26" / 32"	5" / 4"	360 lbs

Features

- 1000 lb. capacity @ 15" and 18" load centers
- Lifting heights - 50" through 78"
- Slip on platforms available
- Solid steel adjustable forks
- Foot operated pump with tip toe release
- Lift time approximately 8" per minute
- Perforated metal safety screen
- Foot-operated safety floor lock
- Leaf type chain with 8250 lbs. yield point
- High impact floor saving phenolic wheels

